

December 1970

Brief 70-10439

# NASA TECH BRIEF



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.

## Laser Method for Finding Axis of Rotation

### The problem:


To determine remotely the axis of rotation of a moving body.

### The solution:

Illuminate the rotating surface with a laser beam and examine the interference patterns resulting from diffused reflections to determine the position of the axis and the direction of motion.

of a viewing lens, the interference patterns in two different planes can be examined.

The interference pattern at any distance from the surface rotates with the surface. For rotation angles greater than a few degrees, the circular streaking is clearly visible. Since all streaks are concentric with the axis, the axis position is that point in the interference pattern where the streaking reduces to zero. If two interference planes at different dis-



### How it's done:

A laser beam is directed toward a diffuse reflecting surface on the rotating object. Light is reflected from the surface as random phase waves which overlap in the region of space in front of the surface and form random ("sparkle") interference patterns that rotate as the object rotates. The interference patterns can be viewed through a lens or recorded on film as circular streaking patterns. With the aid

tances from the surface are examined, the position of the rotational axis can be determined in each plane within an error equal to the width of one bright point in the interference pattern. The accuracy of the axial direction measurement is limited (by diffraction) to an angular error approximately equal to the wavelength divided by the illuminated diameter of the beam at the reflecting surface. A value of  $10^{-4}$  radian for a beam diameter of 10 millimeters can be obtained.

(continued overleaf)

**Note:**

The following documentation may be obtained from:

National Technical Information Service  
Springfield, Virginia 22151  
Single document price \$3.00  
(or microfiche \$0.65)

**Reference:**

NASA-CR-985 (N68-14070), Study of Vibration Measurement by Laser Methods

**Patent status:**

No patent action is contemplated by NASA.

Source: G. A. Massey  
Sylvania Electronic Systems  
under contract to  
Ames Research Center  
(ARC-10388)